



Features

- Industrial Display
- Flat front panel touch screen
- Fanless design
- Wide range DC 9~36V power input
- IP66 compliant front panel / IP69K (option)
- VGA/DVI-D/HDMI/DP input
- System power LED light
- High Brightness LCD and Auto Dimming for option
- Support protective AR glass for option (non-touch version)

Specifications

I/O Port

VGA	1 x VGA
DVI	1 x DVI-D
DP	1 x DP
HDMI	1 x HDMI
Audio	1 x Audio line-in phone jack
OSD Control Membrane	OSD on rear side On board controller, extendable key pad from connector
Power	1 x 3 pins terminal block for DC power input
Others	1 x USB type A for touch control Optional I/O: 1 x Speaker 1 x RS-232 DB-9 for touch control

Standard LCD

Display Type	15" TFT-LCD
Max. Resolution	1024 x 768
Max. Color	262K
Luminance (cd/m ²)	420
View Angle	160(H) / 160(V)
Contrast Ratio	800:1
Backlight Lifetime	30,000 hrs

High Brightness LCD (option)

Display Type	15" TFT-LCD
Max. Resolution	1024 x 768
Max. Color	16.2M
Luminance (cd/m ²)	1000
View Angle	160(H) / 160(V)
Contrast Ratio	800:1
Backlight Lifetime	30,000 hrs

Power

Power Input	DC 9~36V
Power Consumption	MAX: 12.5W (115AR) MAX: 17.6W (115AP)


Touch Screen – Resistive Touch Window Type (Default)

Interface	USB default RS-232 for option
Light Transmission	Over 80%

Touch Screen – Projected Capacitive Type (Option)

Interface	USB
Light Transmission	Over 90%

Dimension



Mechanical

Construction	Aluminum die-casting chassis
Chassis Color	RAL 9007
Mounting	Panel Mount / VESA Mount 100 x 100
IP Rating	IP66 compliant front panel / IP69K (option)
Dimension	410 x 310 x 54.6 mm
Net Weight	4.3 Kg

Environmental

Operating Temperature	0~50°C / -20~60°C for option
Storage Temperature	-30~70 °C
Storage Humidity	10 to 90% @ 40°C, non-condensing
Certificate	CE/FCC Class A

Ordering Information

ARCDIS-115AR-01	15" XGA FPD Industrial display, Resistive touch window, VGA, DVI-D, HDMI, and DP input, 5 keys Rear OSD, DC 9~36V power input with adapter, Aluminum Die-casting Chassis
ARCDIS-115AP-01	15" XGA FPD Industrial display, Projected Capacitive touch screen, VGA, DVI-D, HDMI, and DP input, 5 keys Rear OSD, DC 9~36V power input with adapter, Aluminum Die-casting Chassis